POLY-OVERPACK® 95

Part #: 1237-YE Dimensions: Top Diameter: Ext. / 31.38" / 80 cm

Handling Capacity: 650 lbs. / 295 kg

Int. / 27" / 69 cm Bottom Diameter: Ext / 25.75" / 65 cm Int. / 24.75" / 63 cm Height: Ext. / 41.5" / 105 cm Int. / 37" / 94 cm Weight: 48 lbs. / 21.8 kg Sump Capacity: 95 gal. / 359.6 liters Regulations: UN 1H2/X295/S DOT 49 CFR 173.3(c), EPA, SPCC and NPDES

POLY-OVERPACK® 110

Part #: 1240-YE Dimensions: Top Diameter: Ext. / 31.5" / 80 cm Int. / 27" / 69 cm Bottom Diameter: Ext. / 25.75" / 65 cm Int. / 25" / 63 cm Height: Ext. / 45" / 114 cm Int. / 42" / 107 cm

Weight: 51 lbs. / 23 kg Sump Capacity: 103 gal. / 390 liters Handling Capacity: 650 lbs. / 295 kg Regulations: DOT 49 CFR 173.3(c), EPA, SPCC and NPDES,

DRUM LIFTER

UN 1H2/X295/S

Part #: 3100-BU Weight: 22 lbs. / 9.9 kg Handling Capacity: 1,000 lbs. / 453.7 kg



Roller Technique: Place damaged drum and overpack on their sides with metal rollers underneath drum (i.e. water pipe) Roll drum most of the way inside. Slowly turn overpack upright.

POLY-OVERPACK[®] 95 SALVAGE DRUM IS YOUR OVERPACK REALLY A SALVAGE DRUM?

Our Poly-Overpack[®] 95 meets Group 1 packaging standards and salvage drum regulations. Unlike competing overpacks, Our Poly-Overpack® 95 safely contains a wide range of hazardous materials including: acids, corrosives and damaged parts-in 55-gallon drums.

) ENPAC

Tight, secure and leak-free container closing is simple; place any long object, like a wooden 2x4", in the handy lid slots and turn to screw the lid down tightly.

Meets performance-oriented packaging requirements of US DOT and UN regulations.

> Twist-down lid for safe closure Closed cell gasket in lid

seals closure Castellations in lid allow

for easy closing with pole or wooden 2x4" Double wall lid gives

added strength

Molded area allows for easy gripping and lifting by material handling equipment

Ribbed design provides extra strength

100% UV-protected polyethylene provides protection over a wide range of chemicals



110 AL FOR DISTORTED OR BOWED DRUMS.

Containing irregular drums is not a problem with this handy-sized overpack. With all the great performance features of the Poly-Overpack[®] 95, but built taller to handle misshapen drums.

DRUM LIFIEK

Salvage drum loading is one of the trickiest drum handling jobs. This lifter makes it easy! Unique slim design allows unit to be used where clearance is tight. Works great for general drum handling, too. Jaw has only one moving part, making it practically maintenance free.

- · Lifts open-head or tight-head pails and drums
- · Slim design for loading drums into salvage drums
- 1,000 lb. handling capacity



Angle Roll Technique: Place overpack and drum on side with the two angled in a wide vee. Roll together, working the drum inside the overpack. When inward progress stops, reverse the angle and roll the other way. Turn upright when drum is inside the overpack.



Inverted Overpack Technique: Place damaged drum on overpack lid. Slide overpack over the drum. Rotate upright.



Edition Available See pages 2-3



Upright Overpack Technique: Remove overpack lid while using Part #: 3100-BU to raise and lower drum. Reduces risk and increases use