Omnisports REFERENCE





Technical Characteritics						
Friction	EN 13036-4	80-110				
Shock absorption	EN 14 808	P1	P1	P1		
Vertical deformation	EN 14 809	LT.	r1	L1		
Vertical ball rebound	EN 12235		compliant			

Classification				
Reaction to fire	EN 13501-1	Cfl-S1		

KEY POINTS

Desription:

Vinyl sports floor covering over fibreglass with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

3 types of installation:

- Loose laid (Green Lay)
- Glued Installation
- Installation on Tarkolay

Surface Texture: Sorrent

Compatible Installation:

Association possible with a sub construction (Lumaflex type)

Installation instructions and maintenance guide:

On request

Dimensions (EN ISO 24341):





2 m 20.5 lm or 23 lm

Total thickness (EN ISO 24346):



6.5 mm (± 0,15mm)

Total weight (EN ISO 23997):



4.71 kg/m² (± 500g)

l echnical Characteristics				
Wear Layer	EN 429	0.70 mm		
Resistance to wear	EN ISO 5470-1	≤ 1 g		
Resistance to indentation	EN 1516	compliant < 0.20mm		
Behaviour under a rolling load	EN 1569	< 0.50mm		
		No degradation		
Resistance to impact	EN 1517	No degradation		
·		<u>. </u>		

Specific Characteristics					
Surface treatment	Topclean X-treme performance protection	þ.			
Maintenance					

COMPATIBLE SLABS: Concrete, asphalt screed, anhydrite screed. Any deviation of the slab must be corrected prior installation (6 mm under a 3 m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.

Omnisports Reference



















Manufactured by: Tarkett SA 08203 Sedan - FRANCE









Technical data in force as from the date of publication (02/2016).

The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement.

For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

Tarkett France – 1 terrasse Bellini – Tour Initiale TSA 94200 - 92919 Paris la Défense CEDEX TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com www.professionals.tarkett.com

